

Declaration of Performance

Kemaflex Acryl

Number of Declaration of Performance:

01 S5017 Kemaflex Acryl

1. Unique identification code of the product-type:
01 S5017 Kemaflex Acryl
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):
01 S5017 Kemaflex Acryl
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:
**Sealing compound for facades for internal and external applications.
EN 15651-1:2012 Type F: EXT-INT; 12,5P**
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):
**Kema d.o.o.
Puconci 393
9201 Puconci, Slovenija
Št. proizvodnje: P5001**
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):
-
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
**System 3
System 3 (resistance to fire)**
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:
Notified body ZAG, NB 1404

(name and identification number of the notified body, if relevant)

performed	Testing to	Under system	3
	determine type of		
	sealing compound		

(description of the third party tasks as set out in Annex V)

**And
issued** **Certificate about constancy of performance**

(certificate of constancy of performance, certificate of conformity of the factory production control, test/calculation reports – as relevant)

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

-

(name and identification number of the Technical Assessment Body, if relevant)

Issued

-

(reference number of the European Technical Assessment)

On the

-

basis of

(reference number of the European Assessment Document)

Performed

-

Under system

-

(description of the third party tasks as set out in Annex V)

And

-

issued

(certificate of constancy of performance, certificate of conformity of the factory production control, test/calculation reports – as relevant)

9. Declared performance:

Essential characteristics	Performance	Harmonized technical specification
TYPE F: EXT-INT; 12,5P		
Reaction to fire:	F	EN 15651-1:2012
Release of hazardous chemicals into the environment	N.A.	
Water and Air tightness	N.A.	
Floew resistance	≤ 3 mm	
Reducing the volume	≤ 25%	
Tensile properties after immersion in water	≥ 100%	
Ability to recover	N.A.	
Tensile properties, secant tensile modulus at 23 ° C	N.A.	
Tensile properties, secant tensile modulus at -20 ° C	N.A.	
Tensile properties at a maintained strenght	N.A.	
Adhesion / cohesion properties at variable temperatures	N.A.	
Consistence	Corresponding	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Chief of department of development and quality:

Stanko Polajner univ.dipl.inž.met.

Puconci, 01.09.2015


KEMA Puconci d.o.o.