

Declaration of Performance

KEMAFOB

Number of Declaration of Performance:

01 P5001 KEMAFOB

1. Unique identification code of the product-type:
P5001 KEMAFOB
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):
P5001 KEMAFOB
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:
Surface protection for concrete, hydrophobic impregnation H for Principle 1.1 protection against ingress, Principle 2.1 Moisture control, Principle 8.1 Increasing resistivity.
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):
**Kema d.o.o.
Puconci 393
9201 Puconci, Slovenia
Production No.: P5001**
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):
-
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 2+
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:
EN 1504-2:2004, ITC – Institute for testing and certification, 1023

(name and identification number of the notified body, if relevant)

performed	initial type test, initial inspection of factory and of F.P.C., continuous surveillance assessments and approval of F.P.C.	under system	2+
------------------	---	---------------------	-----------

(description of the third party tasks as set out in Annex V)

and issued **Product Type Examination Report No.: 753500230 TR3/2009,**

Certificate of Factory Production Control No.: 1023-CPR-0137F

(certificate of constancy of performance, certificate of conformity of the factory production control, test/calculation reports – as relevant)

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

-

(name and identification number of the Technical Assessment Body, if relevant)

issued -

(reference number of the European Technical Assessment)

on the basis of -

(reference number of the European Assessment Document)

performed -

under system -

(description of the third party tasks as set out in Annex V)

and issued -

(certificate of constancy of performance, certificate of conformity of the factory production control, test/calculation reports – as relevant)

9. Declared performance:

Essential characteristics	Performance	Harmonized technical specification
Depth of penetration:	Class I, < 10 mm	T.3, EN 1504-2:2004
Absorption ratio AR alc, impact of alkali:	< 7,5%, < 10 %	EN 13580
Drying rate coefficient:	Class I, > 30 %	EN 13579
Loss of mass after freeze-thaw salt stress:	> 20 cycles	EN 1015-11
Dangerous substances:	complies	See MSDS

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

R&D Manager:

Stanko Polajner univ.dipl.inž.met.

Puconci, 30.10.2014


KEMA Puconci d.o.o.