

Declaration of Performance

Kemasan NHL F

Number of Declaration of Performance:

01 P5008 Kemasan NHL F

1. Unique identification code of the product-type:
P5008 Kemasan NHL F
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):
P5008 Kemasan NHL F
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:
Ready mixed mortar for exterior and interior use on walls, ceilings and pillars.
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):
**Kema d.o.o.
Puconci 393
9201 Puconci, Slovenia**
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):
-
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 4
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

(name and identification number of the notified body, if relevant)

performed

(description of the third party tasks as set out in Annex V)

under system

and issued

(certificate of constancy of performance, certificate of conformity of the factory production control, test/calculation reports – as relevant)

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: -

(name and identification number of the Technical Assessment Body, if relevant)

issued

(reference number of the European Technical Assessment)

on the basis of -

(reference number of the European Assessment Document)

performed - under system -

(description of the third party tasks as set out in Annex V)

and issued -

(certificate of constancy of performance, certificate of conformity of the factory production control, test/calculation reports – as relevant)

9. Declared performance:

Essential characteristics	Performance	Harmonized technical specification
Classification	GP – CS I	EN 998-1
Reaction to fire	A1	EN 998-1
Adhesion strenght	$\geq 0,08 \text{ N/mm}^2$	EN 115-12
Compressive strenght	$\geq 1,5 \text{ N/mm}^2$	EN 1015-11
Capillary water absorption	W 0	EN 1015-18
The coefficient of vapour permeability	$\mu < 15$	EN 1015-19
Thermal conductivity	0,47 W/mK (P=50 %); 0,54 W/mK (P=90 %)	EN 1745
Dangerous substances	Complies	See material safety data sheet (MSDS)

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:
Chief of department of development and quality:

Stanko Polajner univ.dipl.inž.met.
Puconci, 12.01.2016

KEMA Puconci d.o.o.