Murexin d.o.o.,
Puconci 393, 9201 Puconci, Slovenia
T: +386 (0)2 545 95 00 | F: +386 (0)2 545 95 10
I: www.murexin.si | E: info@murexin.si

MUREXIN
www.murexin.com

DECLARATION OF PERFORMANCE

in accordance with Annex III to Regulation (EU) No. 182/2011. 305/2011 amended by Delegated Regulation (EU) No. 574/2014

Kemasan 520

No. DOP: 01 P5001 Kemasan 520

1. **Unique identification code of the product-type:**

   01 P5001 Kemasan 520

2. **Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):**

   Production batch number: See product packaging.

3. **Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:**

   Rendering and plastering mortar, GP CS IV – General purpose mortar, for internal and external use on walls, ceilings and columns, acc. to EN 998-1:2017.

4. **Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):**

   Murexin d.o.o.
   Puconci 393
   SI-9201 Puconci, Slovenia

5. **Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):**

6. **System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:**

   Sistem 4

7. **In case of the declaration of performance concerning a construction product covered by a harmonised standard:**

   EN 998-1:2017, ITC Institute for testing and certification, 1023 has conducted a product type test under System 4 and issued: Type Test Report No.: 313500025/2006.

Murexin d.o.o.,
Puconci 393, 9201 Puconci, Slovenia
T: +386 (0)2 545 95 00 | F: +386 (0)2 545 95 10
I: www.murexin.si | E: info@murexin.si

MUREXIN
www.murexin.com

DECLARATION OF PERFORMANCE

in accordance with Annex III to Regulation (EU) No. 182/2011. 305/2011 amended by Delegated Regulation (EU) No. 574/2014

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not relevant

9. Declared performance:

Essential characteristics	Performance	Harmonized technical specification
Class:	GP CS IV	EN 998-1:2017
Compressive strength:	CS IV (≥ 6 N/mm²)	
Adhesion:	≥ 0,2 N/mm²	
Water absorption:	≤ 0,2 kg.m^{-2}min^{0,5} W0 do W2	
Reaction to fire:	A1	
Water wapour permeability μ:	μ < 15	
Thermal conductivity/Density: (tabulated value)	1,17 W/mK (P=50 %); 1,28 W/mK (P=90 %)	
Durability:	10 cycles	
Dangerous substances:	Complies	See MSDS

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.:

Signed for and on behalf of the manufacturer by:

Jernej Kuzmič
Bojan Ošep

Puconci, 18.06.2021

MUREXIN
www.murexin.com
MUREXIN, gradbeni materiali, d.o.o.

Murexin d.o.o.,
Puconci 393, 9201 Puconci, Slovenia
T: +386 (0)2 545 95 00 | F: +386 (0)2 545 95 10
I: www.murexin.si | E: info@murexin.si

MUREXIN
www.murexin.com

DECLARATION OF PERFORMANCE

in accordance with Annex III to Regulation (EU) No. 182/2011. 305/2011 amended by Delegated Regulation (EU) No. 574/2014

CE

06

Murexin d.o.o.
Puconci 393
SI-9201 Puconci, Slovenia

Kemasan 520
No. DOP: 01 P5001 Kemasan 520

Essential characteristics	Performance	Harmonized technical specification
Class:	GP CS IV	EN 998-1:2017
Reaction to fire:	A1	EN 13501-1
Adhesion:	≥ 0,2 N/mm²	EN 998-1:2017
Water absorption:	≤ 0,2 kg.m^{-2}min^{0,5} W0 do W2	
Compressive strength:	CS IV (≥ 6 N/mm²)	
Water wapour permeability:	μ < 15	
Thermal conductivity/Density:	1,17 W/mK (P=50 %); 1,28 W/mK (P=90 %)	
Durability:	10 cycles	
Dangerous substances:	Complies	See MSDS

EN 998-1:2017
Rendering and plastering mortar, GP CS IV – General purpose mortar, for internal and external use on walls, ceilings and columns