

DECLARATION OF PERFORMANCE

*in accordance with Annex III to Regulation (EU) No. 182/2011. 305/2011
amended by Delegated Regulation (EU) No. 574/2014*

Page 1 of 3

Tal M Strong
01 P5001 Tal M Strong

1. Unique identification code of the product-type:

01 P5001 Tal M Strong

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Production batch number: See product packaging.

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Surface protection for industrial floors - Mineral dry shake for concrete floor finishing
acc. to EN 13813 CT – C70 – F10 – A1,5

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Murexin d.o.o.
Puconci 393
SI-9201 Puconci, Slovenia

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

Sistem 4

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

EN 13813:2003, Laboratory Murexin d.o.o. , and IKB PUT Poznan have conducted a product type test under System 4 and issued: Type Test Report No.: 01 P5001 Tal M Strong and Test report No.: 0411/PRJG/0036/2020.

DECLARATION OF PERFORMANCE

*in accordance with Annex III to Regulation (EU) No. 182/2011. 305/2011
amended by Delegated Regulation (EU) No. 574/2014*

Page 2 of 3

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not relevant

9. Declared performance:

Essential characteristics	Performance	Harmonized technical specification
Classification	CT-C70-F10-A1,5	EN 13813:2003
Reaction to fire	Class A1 _{fl}	
Realease of dangerous substances	CT	
Liquid water permeability	NPD	
Water vapour permeability	NPD	
Compressive strength	≥ 70 N/mm ²	
Flexural strength	≥ 10 N/mm ²	
Abrasion Resistance Böhme	A1,5	
Sound insulation	NPD	
Sound absorption	NPD	
Thermal resistance	NPD	
Chemical resistance	NPD	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.:

Signed for and on behalf of the manufacturer by:

Jernej Kuzmič
Bojan Ošep


Puconci, 19.03.2021


MUREXIN
www.murexin.com
MUREXIN, gradbeni materiali, d.o.o.

DECLARATION OF PERFORMANCE

in accordance with Annex III to Regulation (EU) No. 182/2011. 305/2011
amended by Delegated Regulation (EU) No. 574/2014

Page 3 of 3

		
10		
Murexin d.o.o., Puconci 393, 9201 Puconci, Slovenia		
Tal M Strong DoP No.: 01 P5001 Tal M Strong		
Essential characteristics	Performance	Harmonized technical specification
Classification	CT-C70-F10-A1,5	EN 13813:2003
Reaction to fire:	A1 _{fl}	EN 13501-1
Release of corrosive substances (Cementitious Screed):	CT	EN 13813:2003
Liquid water permeability	NPD	
Water vapour permeability	NPD	
Compressive strength:	C70	
Flexural strength:	F10	
Abrasion Resistance		
Böhme:	A1,5	
Sound insulation:	NPD	
Sound absorption:	NPD	
Thermal resistance:	NPD	
Chemical resistance	NPD	
Dangerous substances	Complies	See material safety data sheet (MSDS)
EN 13813:2003 CT-C70-F10-A1,5 Surface protection for industrial floors - Mineral dry shake for concrete floor finishing		