

# ARTCOLOR SPARK, GOLD, SILVER

Additive for epoxy mortar KEMAPOX ARTCOLOR



## PRODUCT DESCRIPTION

The ARTCOLOR ADDITIVE can be mixed together with the two-part epoxy mortar KEMAPOX ARTCOLOR, enable to get grouts with unique and exclusive effects without prejudicing the ease of cleaning of the product. These additive is available separately, in pre-batched packages.

ARTCOLOR ADDITIVE can be added to any colour of the epoxy mortar KEMAPOX ARTCOLOR to get "shiny, silver or gold" effect. (In comparison with the original colour without additive, the color will not change)

**FIELD OF USE** Special additive for the two-part epoxy mortar KEMAPOX ARTCOLOR suitable for grouting floor and wall tiles, gres stoneware, mosaics, clinker in interiors rooms such as: bathrooms, kitchens, floors and shops, columns...

## PRODUCT DATA

**Packing** 1 x 75 g in plastic bucket

**Storage and expiration date** 12 months from date of production if stored properly in undamaged original sealed packaging in dry and cool conditions. Date of production is printed on packaging.

## INSTRUCTIONS FOR USE

**CONSUMPTION** Additive is available separately, in pre-measured packages ready to use in each 2,5 kg KEMAPOX ARTCOLOR bucket.

**INSTALLATION**

1. Mix part B (catalyst) with part A (coloured paste) of the KEMAPOX ARTCOLOR using an electric drill equipped with mixing paddle until a uniform, lump-free mix is obtained.
2. Pour the third component ARTCOLOR ADDITIVE , already pre-batched in its package and mix till getting a smooth mixture.

**APPLICATION** Introduce the mortar into the joints using a rubber float and clean with water following the instructions on the packaging.

**COAGULATION** /

## LIMITATIONS

**BASE TEMPERATURE** +5°C min./ +30°C max.

**AIR TEMPERATURE** +5°C min./ +30°C max.

**MATERIAL TEMPERATURE** +5°C min./ +30°C max.

- WARNINGS**
- Do not apply the epoxy mortar KEMAPOX ARTCOLOR mixed with the component ARTCOLOR ADDITIVE on ceramic surfaces in contact with chemical weapons such as on industrial floorings.
  - Handle the additives with care since they have a very low specific weight and so the dust particles can rise up in the air.
  - If the ceramic tiles are exposed to sunlight or artificial light, the effects you can get with these additives stand out more.

**Recommendation:** Remains of the material have to be removed in accordance with the legislation.

**Data source:** All technical data in this technical sheet was obtained by laboratory research. Actual data may differ due to different working conditions.

**Local restrictions:** Due to specific local regulations the installed product can differ from country to country. For exact instructions for use a country specific technical sheet should be obtained.

## SAFETY DATA

More data on storage, handling and use of mixture can be found in the safety sheet which contains safety, toxicological and ecological data. Warnings on the original packaging should also be considered.

## LEGAL BASE

Information and recommendations related to use of KEMA products are presented in good faith and believed to be correct. The later is based on our knowledge and experience with the products. Information is supplied upon the condition that products are stored and used according to the recommendations and the persons receiving the same will make their own determination as to its suitability for their purposes prior to use. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to Information or the product to which information refers. In no event will KEMA be responsible for damages of any nature whatsoever resulting from the use of or reliance upon Information or the product to which Information refers. Nothing contained herein is to be construed as a recommendation to the use any product, process, equipment or formulation in conflict with any patent, and KEMA makes no representation or warranty, expressed or implied that the use thereof will not infringe any patent. All orders fall under current sales and supply conditions. The user should always check the latest technical sheet available upon demand.