



KEMA d.o.o.,
Puconci 393, 9201 Puconci, Slovenija
T: +386 (0)2 545 95 00, F: +386 (0)2 545 95 10
Technical consulting: +386 (0)2 545 95 28, +386 (0)2 545 95 73
I: www.kema-on.net | E: info@kema.si

Label: TL_Artcolor_clean_gel
Revision: June 2017
ID: 575

TECHNICAL DATA SHEET

ARTCOLOR CLEANER GEL

Concentrated cleaning agent for the removal of residues of epoxy mortar



PRODUCT DESCRIPTION

ARTCOLOR CLEANER is concentrated liquid and slightly alkaline cleaning agent for use on all types of ceramic tiles, including the most vulnerable, such as porcelain and glass mosaic and all types of natural stones.

Field of use

Also suitable for removing stains and cleaning heavily soiled floors and ceramic tiles. For the removal of epoxy mortar use undiluted, for the cleaning of dirt it must be diluted with water in a ratio of from 1:10 to 3:10.

Product properties

- ARTCOLOR CLEANER gel has a higher viscosity and is designed for cleaning vertical surfaces

PRODUCT DATA

Basic information

Appearance	thick transparent liquid
Packing	0,75/1 12 plastic cans/cardbox 44 cardbox/pallet
Storage and expiration date	24 months from date of manufacture when stored properly in a dry place, in original, unopened and undamaged packaging. Protect from heat sources and direct sunlight. Protect from freezing. The date of manufacture stamped on the packaging.

Technical data

Color	Color-less
Odour	Peach
Flammability	No
Customs Code	3402 90 90
Specific weight	1010 ± 10 g/l
Tme needed for surface treatment	approx.: 10-15 min
pH value	12 ± 0,5

INSTRUCTIONS FOR USE

Consumption

10-15 m²/l

Installation

Pour on the surface in pure or diluted form and leave on for 10-15 minutes. Then rub the surface with a brush or white fleece KEMAPOX Whip. Pick up the cleaning agent with a sponge, rubber wiper or vacuum liquids. Then rinse with plenty of clean water and immediately wipe with a clean cloth. Do not wait to rinsing water evaporate, because in this way the resulting marks on the ceramic surface.

Tme needed for surface treatment

approx.: 10-15 min.

LIMITATIONS

Base temperature +5°C min./ +35°C max.

Air temperature +5°C min./ +35°C max.

Material temperature +5°C min./ +35°C max.

Warnings

- Before use protect doors, windows, rubber seals, furniture and all the surfaces that could be in a direct contact with the product. It may cause damages.
- During cleaning frequently change the water.
- The product can cause irritation.
- While using the product keep wearing suitable protective clothing (rubber gloves, mask and goggles). Follow the instructions listed in the technical and safety data sheet.
- In the event of accidental spillage, the product is absorbed by the absorbent means (paper, sawdust, vermiculite, etc.) and transfer to a container for disposal according to local / national regulations

Recommendation: Remains of the product must be disposed of in accordance with local regulations.

Data source: All technical data in this technical sheet was obtained by laboratory research. Actual data may vary due to circumstances beyond our control.

Local restrictions: We emphasize that due to specific local regulations the installed product can vary from country to country. For exact application a specific technical sheet should be obtained.

SAFETY DATA

Information required pursuant to Directive 1907/2006 / EC (REACH), Article 31

Xi-Irritant.

R 36 - Irritating to eyes.

R 38 - Irritating to the skin.

S 2 - Keep out of reach of children.

S 24 - Avoid contact with skin.

S 25 - Avoid contact with eyes.

S 26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Further information on storage, handling and use of the product can be found in the safety sheet which contains safety, toxicological and ecological data, and also pay attention to the warnings on the original packaging.

LEGAL BASE

Information and recommendations related to use of KEMA products are presented in good faith and believed to be correct. The later is based on our knowledge and experience with the products. Information is supplied upon the condition that products are stored and used according to the recommendations and the persons receiving the same will make their own determination as to its suitability for their purposes prior to use. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to Information or the product to which information refers. In no event will KEMA be responsible for damages of any nature whatsoever resulting from the use of or reliance upon Information or the product to which Information refers. Nothing contained herein is to be construed as a recommendation to the use any product, process, equipment or formulation in conflict with any patent, and KEMA makes no representation or warranty, expressed or implied that the use thereof will not infringe any patent. All orders fall under current sales and supply conditions. The user should always check the latest technical sheet available upon demand.