

FUGA SAND 200

Quartz sand for grouting of paving units, washed tiles, etc.

- Nature quartz sand
- ▶ Remarkably mechanical properties
- ▶ Correct grain-size distribution
- Sieved
- ▶ 100% washed, harmlessness



PRODUCT DESCRIPTION	Quartz sand for grouting of paving units, floor tiles, washed tiles, etc., of 1-2 mm grain sizes.	
FIELD OF USE	OF USE Flame-dried quartz sand for grouting of paving units, floor tiles, washed boards etc Due to the excellent flowability	
	and correct granulation composition, it assures easy and quality grouting.	

PRODUCT • Nature quartz sand

- **PROPERTIES** Remarkably mechanical properties
 - Correct grain-size distribution
 - Sieved
 - 100% washed, harmlessness

PRODUCT DATA		
BASIC	Appearance	White sand
INFORMATION		
	Packing	25 kg v PE bag / 1000 kg (40x25 kg) on palette
	Storage and expiration date	Unlimited from date of production if stored properly in undamaged original sealed packaging in dry and cool conditions. Date of production is printed on packaging.





Grain Size	1-2 mm
Hardness (Mohs)	7
Ignition loss	< 0,03 %
Sintering point	> 1500 °C
Softening point	> 1720 °C
Uncompacted bulk density	1390 kg/m³ according to grain size
Moisture	< 0,2 % dried quartz sand

PROPERTIES

SiO ₂	> 99 %
Fe ₂ O ₃	0,297 %
Al_2O_3	0,658 %
TiO ₂	0,032 %
CaO	0,041 %
MgO	0,027 %
P ₂ O ₅	0,009 %
K ₂ O	0,104 %

CHEMICAL COMPOSITION

INSTRUCTIONS FOR USE

CONSUMPTION Depending on the length, width and dept of paving units ot cement based floor tiles, etc...

LIMITATIONS

Data source: All technical data in this technical sheet was obtained by laboratory research. Actual data may differ due to different working conditions.

Local restrictions: Due to specific local regulations the installed product can differ from country to country. For exact instructions for use a country specific technical sheet should be obtained.

PROOFS

NORMS/STANDARDS In accordance with EN 13139:2002, report No.: P 171-AGR-04. igmat d.d., Ljubljana - Polje, Slovenia.



SAFETY DATA

More data on storage, handling and use of mixture can be found in the safety sheet which contains safety, toxicological and ecological data. Warnings on the original packaging should also be considered.

LEGAL BASE

Information and recommendations related to use of KEMA products are presented in good faith and believed to be correct. The later is based on our knowledge and experience with the products. Information is supplied upon the condition that products are stored and used according to the recommendations and the persons receiving the same will make their own determination as to its suitability for their purposes prior to use. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to Information or the product to which information refers. In no event will KEMA be responsible for damages of any nature whatsoever resulting from the use of or reliance upon Information or the product to which Information refers. Nothing contained herein is to be construed as a recommendation to the use any product, process, equipment or formulation in conflict with any patent, and KEMA makes no representation or warranty, expressed or implied that the use thereof will not infringe any patent. All orders fall under current sales and supply conditions. The user should always check the latest technical sheet available upon demand.

Label: TL_Fug_Sand_200 Issue: OCTOBER 2016 Revision: August 2019 ID: 645

ID: 645 TDS: FUGA SAND 200