Printing date 11.01.2017 Revision: 11.01.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- . 1.1 Product identifier
- · Trade name: KEMAPUR V 7000 M B
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Construction chemicals
- . 1.3 Details of the supplier of the safety data sheet
- . Manufacturer/Supplier:

KEMA d.o.o.

Puconci 393

9201 Puconci

Slovenija

- · Further information obtainable from: R&D DEPARTMENT
- . 1.4 Emergency telephone number: +386 (0)2 545 95 00

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 1 H226 Flammable liquid and vapour.



GHS08 health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.



GHS07

Acute Tox. 4 H312 Harmful in contact with skin.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Storage: Store in a well closed container, protected from light, moisture and air at room temperature.
- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02

IS02 GHS07

GHS08

- · Signal word Danger
- Hazard-determining components of labelling: xylene

(Contd. on page 2)

Printing date 11.01.2017 Revision: 11.01.2017

Trade name: KEMAPUR V 7000 M B

(Contd. of page 1)

Hexamethylene diisocyanate, oligomers

ethylbenzene

hexamethylene-di-isocyanate

· Hazard statements

H226 Flammable liquid and vapour.

H312+H332 Harmful in contact with skin or if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P285 In case of inadequate ventilation wear respiratory protection.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves / eye protection / face protection.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- · 2.3 Other hazards
- . Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 28182-81-2	Hexamethylene diisocyanate, oligomers ♦ Skin Sens. 1, H317	25-50
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9	xylene Flam. Liq. 3, H226 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	10-25
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226	10-25
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1	N-Butyl Acetate Flam. Liq. 3, H226 STOT SE 3, H336	10-25
CAS: 100-41-4 EINECS: 202-849-4 Index number: 601-023-00-4	ethylbenzene Flam. Liq. 2, H225 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H332	<i>≤</i> 2,5
CAS: 822-06-0 EINECS: 212-485-8 Index number: 615-011-00-1	hexamethylene-di-isocyanate Acute Tox. 3, H331 Resp. Sens. 1, H334 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	<i>≤</i> 2,5%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

Printing date 11.01.2017 Revision: 11.01.2017

Trade name: KEMAPUR V 7000 M B

(Contd. of page 2)

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- . Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- . 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

. 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

(Contd. on page 4)

Printing date 11.01.2017 Revision: 11.01.2017

Trade name: KEMAPUR V 7000 M B

(Contd. of page 3)

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- . Storage.
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Do not seal receptacle gas tight.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

. 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- . 8.1 Control parameters

	require monitoring	

1330-20-7 xylene

IOELV Short-term value: 442 mg/m³, 100 ppm

Long-term value: 221 mg/m³, 50 ppm

Skin

108-65-6 2-methoxy-1-methylethyl acetate

IOELV Short-term value: 550 mg/m³, 100 ppm

Long-term value: 275 mg/m³, 50 ppm

Skin

100-41-4 ethylbenzene

IOELV Short-term value: 884 mg/m³, 200 ppm

Long-term value: 442 mg/m³, 100 ppm

Skin

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 5)

Printing date 11.01.2017 Revision: 11.01.2017

Trade name: KEMAPUR V 7000 M B

(Contd. of page 4)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

. Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

SECTION	9: Physical	and chemical	properties

. 9.1 Information on basic physical and chemical properties

. General Information

· Appearance:

Form: Liquid

Colour: According to product specification

Odour: Characteristic
 Odour threshold: Not determined.

· pH-value: Not determined.

. Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: /

. Flash point: >21 °C · Flammability (solid, gas): Not applicable. 315 °C . Ignition temperature: Not determined. . Decomposition temperature: Product is not selfigniting. · Auto-ignition temperature: . Explosive properties: Product is not explosive. However, formation of explosive air/ vapour mixtures are possible. Explosion limits: Lower: 1,1 Vol %

 Lower:
 1,1 Vol %

 Upper:
 10,8 Vol %

· Vapour pressure at 20 °C: 10,7 hPa

• Density at 20 °C: 0,955 g/cm³

Relative density Not determined.

(Contd. on page 6)

Printing date 11.01.2017 Revision: 11.01.2017

Trade name: KEMAPUR V 7000 M B

		(Contd. of page 5
· Vapour density	Not determined.	
· Evaporation rate	Not determined.	
. Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
. Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:		
VOC (EC)	382 g/l	
. 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- . 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- . 11.1 Information on toxicological effects
- · Acute toxicity

Harmful in contact with skin or if inhaled.

. LD/LC50 values relevant for classification:			
ATE (Acu	ATE (Acute Toxicity Estimates)		
Dermal	LD50	13333 mg/kg (Rabbit)	
Inhalative	LC50/4 h	64,5 mg/l	
1220 20 7	1220 20 7		

1330-20-7 xylene		
Oral	<i>LD50</i>	4300 mg/kg (Rat)
Dermal	<i>LD50</i>	2000 mg/kg (Rabbit)
Inhalative	LC50/4 h	11 mg/l (ATE)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- . Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.

(Contd. on page 7)

Printing date 11.01.2017 Revision: 11.01.2017

Trade name: KEMAPUR V 7000 M B

(Contd. of page 6)

- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- . 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- . 12.5 Results of PBT and vPvB assessment
- . **PBT:** Not applicable.
- . vPvB: Not applicable.
- . 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- . 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- . Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

- . 14.1 UN-Number
- · ADR,RID,ADN, IMDG, IATA

UN1263

- · 14.2 UN proper shipping name
- · IMDG, IATA

PAINT RELATED MATERIAL

- . 14.3 Transport hazard class(es)
- . ADR/RID/ADN



Class 3 (F1) Flammable liquids.

(Contd. on page 8)

Printing date 11.01.2017 Revision: 11.01.2017

Trade name: KEMAPUR V 7000 M B

	(Contd. of pag
Label	3
IMDG, IATA	
3	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR,RID,ADN, IMDG, IATA	III
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	30
EMS Number:	F-E, <u>S-E</u>
Stowage Category	A
14.7 Transport in bulk according to Ann	
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR/RID/ADN	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
Transport category	Maximum net quantity per outer packaging: 1000 ml 3
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
• • • • •	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	Void

SECTION 15: Regulatory information

- . 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- . Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5a FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 10 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

Printing date 11.01.2017 Revision: 11.01.2017

Trade name: KEMAPUR V 7000 M B

(Contd. of page 8)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

. Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

· Department issuing SDS: R&D DEPARTMENT

· Abbreviations and acronyms:

ADR: Acc ord e uropéen sur le transport des marchandises dan gereuses par Route (Europe an Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 1: Flammable liquids – Category 1

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 3: Acute toxicity – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Resp. Sens. 1: Respiratory sensitisation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1