## Safety data sheet

P

according to 1907/2006/EC, Article 31	
-	Revision: 11.01.2017
SECTION 1: Identification of the substance/mixture and of the company/un	dertaking
<ul> <li>1.1 Product identifier</li> <li>Trade name: <u>KEMAPUR V 7000 B</u></li> <li>1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.</li> <li>Application of the substance / the mixture Construction chemicals</li> </ul>	
<ul> <li>1.3 Details of the supplier of the safety data sheet</li> <li>Manufacturer/Supplier: KEMA d.o.o. Puconci 393</li> <li>9201 Puconci Slovenija</li> </ul>	
<ul> <li>Further information obtainable from: R&amp;D DEPARTMENT</li> <li>1.4 Emergency telephone number: +386 (0)2 545 95 00</li> </ul>	
SECTION 2: Hazards identification	
<ul> <li>2.1 Classification of the substance or mixture</li> <li>Classification according to Regulation (EC) No 1272/2008</li> <li>GHS02 flame</li> <li>Flam. Liq. 1 H226 Flammable liquid and vapour.</li> <li>GHS08 health hazard</li> <li>Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhal</li> </ul>	led.
<i>Acute Tox. 4 H312 Harmful in contact with skin.</i> <i>Acute Tox. 4 H332 Harmful if inhaled.</i> <i>Skin Sens. 1 H317 May cause an allergic skin reaction.</i> <i>Storage: Store in a well closed container, protected from light, moisture and air at room ten</i>	nperature
<ul> <li>2.2 Label elements</li> <li>Labelling according to Regulation (EC) No 1272/2008</li> <li>The product is classified and labelled according to the CLP regulation.</li> <li>Hazard pictograms</li> </ul>	<i>p</i>
GHS02 GHS07 GHS08	
· Signal word Danger	
• Hazard-determining components of labelling: xylene	(Contd. on page 2)

Printing date 11.01.2017

Revision: 11.01.2017

Trade name: KEMAPUR V 7000 B

	(Contd. of page 1)
Hexameth	ylene diisocyanate, oligomers
ethylbenz	ene
•	ylene-di-isocyanate
· Hazard s	
H226	Flammable liquid and vapour.
H312+H.	332 Harmful in contact with skin or if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
· Precautio	onary statements
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P3	61+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P285	In case of inadequate ventilation wear respiratory protection.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
	f PBT and vPvB assessment
• <b>PBT:</b> Not	t applicable.

· **vPvB:** Not applicable.

#### SECTION 3: Composition/information on ingredients

. 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

CAS: 28182-81-2	Hexamethylene diisocyanate, oligomers	25-50%
EINECS: 215-535-7	xylene Flam. Liq. 3, H226 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	10-25%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226	10-25%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1	N-Butyl Acetate Flam. Liq. 3, H226 STOT SE 3, H336	10-25%
CAS: 100-41-4 EINECS: 202-849-4 Index number: 601-023-00-4	ethylbenzene Flam. Liq. 2, H225 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H332	<i>≤</i> 2,5%
CAS: 822-06-0 EINECS: 212-485-8 Index number: 615-011-00-1	<ul> <li>hexamethylene-di-isocyanate</li> <li>Acute Tox. 3, H331</li> <li>Resp. Sens. 1, H334</li> <li>Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335</li> </ul>	<i>≤</i> 2,5%

EU

Printing date 11.01.2017

Revision: 11.01.2017

Trade name: KEMAPUR V 7000 B

(Contd. of page 2)

• Additional information: For the wording of the listed hazard phrases refer to section 16.

#### **SECTION 4: First aid measures**

. 4.1 Description of first aid measures

• General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation:
- Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.

. 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

- . 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

#### **SECTION 5: Firefighting measures**

- 5.1 Extinguishing media
- Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- . 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- . 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

#### **SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

• 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

#### **SECTION 7: Handling and storage**

• 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care.

(Contd. on page 4)

EU

Printing date 11.01.2017

Revision: 11.01.2017

#### Trade name: KEMAPUR V 7000 B

(Contd. of page 3)

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges. Keep respiratory protective device available.

• 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles: Store in a cool location.

· Information about storage in one common storage facility: Not required.

· Further information about storage conditions:

Keep container tightly sealed. Do not seal receptacle gas tight. Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

• 7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

8.1	Control	parameters
-----	---------	------------


0	ients with limit values that require monitoring at the workplace: 0-7 xylene
IOELV	Short-term value: 442 mg/m³, 100 ppm Long-term value: 221 mg/m³, 50 ppm Skin
108-65-	-6 2-methoxy-1-methylethyl acetate
IOELV	Short-term value: 550 mg/m³, 100 ppm Long-term value: 275 mg/m³, 50 ppm Skin
100-41-	4 ethylbenzene
IOELV	Short-term value: 884 mg/m³, 200 ppm Long-term value: 442 mg/m³, 100 ppm Skin
Additio	nal information: The lists valid during the making were used as basis.
Persona General Keep av Immedia Wash h Avoid ca <b>Respira</b> In case	posure controls al protective equipment: al protective and hygienic measures: way from foodstuffs, beverages and feed. ately remove all soiled and contaminated clothing hands before breaks and at the end of work. contact with the eyes and skin. <b>tory protection:</b> of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure of content device.
	f-contained respiratory protective device.

Printing date 11.01.2017

Revision: 11.01.2017

#### Trade name: KEMAPUR V 7000 B

(Contd. of page 4)





Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation . Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

9.1 Information on basic physical and che	emical properties
General Information	
Appearance: Form:	Liquid
Form: Colour:	Liquid According to product specification
Odour:	According to product specification Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition Melting point/freezing point: Initial boiling point and boiling range:	Undetermined. Undetermined.
Flash point:	>21 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	315 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air vapour mixtures are possible.

Printing date 11.01.2017

Revision: 11.01.2017

Trade name: KEMAPUR V 7000 B

	(Contd. o	f page
· Explosion limits:		
Lower:	1,1 Vol %	
Upper:	10,8 Vol %	
· Vapour pressure at 20 •C:	10,7 hPa	
Density at 20 °C:	0,955 g/cm <sup>3</sup>	
· Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
· Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:		
VOC (EC)	382 g/l	
9.2 Other information	No further relevant information available.	

#### **SECTION 10: Stability and reactivity**

. 10.1 Reactivity No further relevant information available.

. 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

#### **SECTION 11: Toxicological information**

· 11.1 Information on toxicological effects

· Acute toxicity

Harmful in contact with skin or if inhaled.

· LD/LC50	values relev	vant for classification:
ATE (Acu	te Toxicity	Estimates)
Dermal	LD50	13333 mg/kg (Rabbit)
Inhalative	LC50/4 h	64,5 mg/l
1330-20-7	xylene	
Oral	LD50	4300 mg/kg (Rat)
Dermal	LD50	4300 mg/kg (Rat) 2000 mg/kg (Rabbit)
Inhalative	LC50/4 h	11 mg/l (ATE)
		(Contd. on page 7)

Printing date 11.01.2017

Revision: 11.01.2017

(Contd. of page 6)

Trade name: KEMAPUR V 7000 B

#### • Primary irritant effect:

- . Skin corrosion/irritation Based on available data, the classification criteria are not met.
- . Serious eye damage/irritation Based on available data, the classification criteria are not met.
- *Respiratory or skin sensitisation* May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- . Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- . Reproductive toxicity Based on available data, the classification criteria are not met.
- . STOT-single exposure Based on available data, the classification criteria are not met.
- . STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

#### **SECTION 12: Ecological information**

#### . 12.1 Toxicity

- · Aquatic toxicity: No further relevant information available.
- . 12.2 Persistence and degradability No further relevant information available.
- . 12.3 Bioaccumulative potential No further relevant information available.
- . 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- . 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- **vPvB:** Not applicable.
- . 12.6 Other adverse effects No further relevant information available.

#### **SECTION 13: Disposal considerations**

- . 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packaging:
- . Recommendation: Disposal must be made according to official regulations.

# SECTION 14: Transport information · 14.1 UN-Number · ADR,RID,ADN, IMDG, IATA UN1263 · 14.2 UN proper shipping name · IMDG, IATA PAINT RELATED MATERIAL

Printing date 11.01.2017

Revision: 11.01.2017

Trade name: KEMAPUR V 7000 B

	(Contd. of pa
14.3 Transport hazard class(es)	
ADR/RID/ADN	
3	
Class	3 (F1) Flammable liquids.
Label	3
IMDG, IATA	
3	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, RID, ADN, IMDG, IATA	III
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	30
EMS Number:	<i>F-E</i> , <u><i>S-E</i></u>
Stowage Category	Α
14.7 Transport in bulk according to Ann	
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR/RID/ADN	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
<b>T</b>	Maximum net quantity per outer packaging: 1000 ml
Transport category	3 D/F
Tunnel restriction code	<i>D/E</i>
IMDG	51
Limited quantities (LQ)	5L Code: E1
Excepted quantities (EQ)	Coae: E1 Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
TINT HAMA JAL DAMA LACE WILL	
UN "Model Regulation":	Void

(Contd. on page 9)

Printing date 11.01.2017

Revision: 11.01.2017

Trade name: KEMAPUR V 7000 B

(Contd. of page 8)

#### **SECTION 15: Regulatory information**

. 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5a FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 10 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50 t
- . REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- . 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

#### · Department issuing SDS: R&D DEPARTMENT

#### Abbreviations and acronyms:

ADR: Acc ord e uropéen sur le transport des marchandises dan gereuses par Route (Europe an Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 1: Flammable liquids - Category 1 Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity - Category 4 Acute Tox. 3: Acute toxicity – Category 3 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Resp. Sens. 1: Respiratory sensitisation – Category 1 Skin Sens. 1: Skin sensitisation - Category 1 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard - Category 1