Printing date 11.01.2017 Revision: 11.01.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- . 1.1 Product identifier
- · Trade name: KEMAPUR V 7000 A
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Construction chemicals
- · 1.3 Details of the supplier of the safety data sheet
- . Manufacturer/Supplier:

KEMA d.o.o.

Puconci 393

9201 Puconci

Slovenija

- · Further information obtainable from: R&D DEPARTMENT
- . 1.4 Emergency telephone number: +386 (0)2 545 95 00

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

Acute Tox. 4 H312 Harmful in contact with skin.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

- · Storage: Store in a well closed container, protected from light, moisture and air at room temperature.
- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02

2 GHS07

- · Signal word Warning
- · Hazard-determining components of labelling:

xylene

ethylbenzene

. Hazard statements

H226 Flammable liquid and vapour.

H312+H332 Harmful in contact with skin or if inhaled.

H315 Causes skin irritation.

(Contd. on page 2)

Printing date 11.01.2017 Revision: 11.01.2017

Trade name: KEMAPUR V 7000 A

(Contd. of page 1)

. Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P241 Use explosion-proof electrical/ventilating/lighting equipment.
P280 Wear protective gloves / eye protection / face protection.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

. 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.*vPvB*: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9	xylene Flam. Liq. 3, H226 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	25-50%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1	N-Butyl Acetate Flam. Liq. 3, H226 STOT SE 3, H336	10-25%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226	10-25%
CAS: 100-41-4 EINECS: 202-849-4 Index number: 601-023-00-4	ethylbenzene Flam. Liq. 2, H225 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H332	≤ 2,5%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- . General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

. After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.

(Contd. on page 3)

Printing date 11.01.2017 Revision: 11.01.2017

Trade name: KEMAPUR V 7000 A

(Contd. of page 2)

- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- . 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- . 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

. 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Open and handle receptacle with care.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- . Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

(Contd. on page 4)

Printing date 11.01.2017 Revision: 11.01.2017

Trade name: KEMAPUR V 7000 A

(Contd. of page 3)

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- . 8.1 Control parameters

. Ingredients with limit values that require monitoring at the workplace:

1330-20-7 xylene

IOELV Short-term value: 442 mg/m³, 100 ppm Long-term value: 221 mg/m³, 50 ppm

Skin

108-65-6 2-methoxy-1-methylethyl acetate

IOELV Short-term value: 550 mg/m³, 100 ppm Long-term value: 275 mg/m³, 50 ppm Skin

100-41-4 ethylbenzene

IOELV Short-term value: 884 mg/m³, 200 ppm Long-term value: 442 mg/m³, 100 ppm

Skin

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- . Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

Printing date 11.01.2017 Revision: 11.01.2017

Trade name: KEMAPUR V 7000 A

(Contd. of page 4)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

. Eye protection:



Tightly sealed goggles

9.1 Information on basic physical and che	emical properties
General Information Appearance:	
Form:	Liquid
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	Undetermined.
Flash point:	>21 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	315 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive ai
	vapour mixtures are possible.
Explosion limits:	
Lower:	1,1 Vol %
Upper:	10,8 Vol %
Vapour pressure at 20 °C:	10,7 hPa
Density:	Not determined.
Relative density	0,983 g/l
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.

(Contd. on page 6)

Printing date 11.01.2017 Revision: 11.01.2017

Trade name: KEMAPUR V 7000 A

(Contd. of page 5)

Kinematic: Not determined.

. Solvent content:

Organic solvents:

9.2 Other information

VOC (EC)

No further relevant information available.

SECTION 10: Stability and reactivity

- . 10.1 Reactivity No further relevant information available.
- . 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

Harmful in contact with skin or if inhaled.

· LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

 Dermal
 LD50
 7843 mg/kg (Rabbit)

 Inhalative
 LC50/4 h
 40,7 mg/l

1330-20-7 xylene

Oral	LD50	4300 mg/kg (Rat)
Dermal	<i>LD50</i>	2000 mg/kg (Rabbit)
Inhalative	LC50/4 h	11 mg/l (ATE)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

EU

Printing date 11.01.2017 Revision: 11.01.2017

Trade name: KEMAPUR V 7000 A

(Contd. of page 6)

SECTION 12: Ecological information

- . 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- . General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- . 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- . Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- . Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

- · 14.1 UN-Number
- · ADR, RID, ADN, IMDG, IATA

UN1263

- . 14.2 UN proper shipping name
- · IMDG, IATA

PAINT RELATED MATERIAL

- · 14.3 Transport hazard class(es)
- · ADR/RID/ADN



. Class

3 (F1) Flammable liquids.

. Label

3

· IMDG, IATA



Class

3 Flammable liquids.

(Contd. on page 8)

Printing date 11.01.2017 Revision: 11.01.2017

Trade name: KEMAPUR V 7000 A

	(Contd. of pa
Label	3
14.4 Packing group ADR,RID,ADN, IMDG, IATA	III
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	30
EMS Number:	F-E, <u>S-E</u>
Stowage Category	A
14.7 Transport in bulk according to Anne	ex II of
Marpol and the IBC Code	Not applicable.
$Transport/Additional\ information:$	
ADR/RID/ADN	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, 3, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- . Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

. Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

(Contd. on page 9)

Printing date 11.01.2017 Revision: 11.01.2017

Trade name: KEMAPUR V 7000 A

(Contd. of page 8)

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

· Department issuing SDS: R&D DEPARTMENT

· Abbreviations and acronyms:

ADR: Accord e uropéen sur le transport des marchandises dan gereuses par Route (Europe an Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

EU