Safety data sheet

according to 1907/2006/EC, Article 31	
Printing date 17.10.2016	Revision: 18.07.2017
SECTION 1: Identification of the substance/mixture and of the compa	ny/undertaking
· 1.1 Product identifier	
• Trade name: <u>KEMASAN 520</u> • 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. • Application of the substance / the mixture Construction chemicals	
 1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier: KEMA d.o.o. Puconci 393 9201 Puconci Slovenija 	
 Further information obtainable from: R&D DEPARTMENT 1.4 Emergency telephone number: +386 (0)2 545 95 00 	
SECTION 2: Hazards identification	
 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 GHS05 corrosion Eye Dam. 1 H318 Causes serious eye damage. GHS07 Skin Irrit. 2 H315 Causes skin irritation. Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause a Storage: Well-closed original packaging 	respiratory irritation.
 2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. Hazard pictograms GHS05 GHS07 	
· Signal word Danger	
 Hazard-determining components of labelling: Cement, portland, chemicals calcium dihydroxide Hazard statements H318 Causes serious eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H335 May cause respiratory irritation. Precautionary statements P101 If medical advice is needed, have product container or label at han P102 Keep out of reach of children. 	<i>d</i> .

P103 P261 Read label before use. Avoid breathing dust/fume/gas/mist/vapours/spray.

(Contd. on page 2)

EU

Printing date 17.10.2016

Revision: 18.07.2017

Trade name: KEMASAN 520

	(Contd. of page 1)
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338	B IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P321	Specific treatment (see on this label).
P501	Dispose of contents/container in accordance with local/regional/national/international
	regulations.
· 2.3 Other hazards	

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous compon	ents:	
	Cement, portland, chemicals	2,5-10%
EINECS: 266-043-4	 Eye Dam. 1, H318 Skin Irrit. 2, H315; Skin Sens. 1A, H317; STOT SE 3, H335 	
	() Skin Irrit. 2, H315; Skin Sens. 1A, H317; STOT SE 3, H335	
	calcium dihydroxide	2,5-10%
EINECS: 215-137-3	♦ Eye Dam. 1, H318	
· Additional informat	tion: For the wording of the listed hazard phrases refer to section 16.	

SECTION 4: First aid measures

• 4.1 Description of first aid measures

· General information: Immediately remove any clothing soiled by the product.

• After inhalation:

- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

(Contd. on page 3)

EU

Printing date 17.10.2016

Revision: 18.07.2017

(Contd. of page 2)

Trade name: KEMASAN 520

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- \cdot 6.3 Methods and material for containment and cleaning up:

Use neutralising agent. Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

- · 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling Thorough dedusting. Ensure good ventilation/exhaustion at the workplace.

- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Store in dry conditions.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:
- 1305-62-0 calcium dihydroxide
- IOELV Long-term value: 5 mg/m³
- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.
- Respiratory protection:
- In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 4)

EU -

Printing date 17.10.2016

Revision: 18.07.2017

(Contd. of page 3)

Trade name: KEMASAN 520

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation \cdot *Material of gloves*

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.





Tightly sealed goggles

9.1 Information on basic physical a	und chemical properties	
General Information		
Appearance:		
Form:	Powder	
Colour:	According to product specification	
Odour:	Characteristic	
Odour threshold:	Not determined.	
pH-value at 20 °C:	11	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	Undetermined.	
Flash point:	>100 °C	
Flammability (solid, gaseous):	Not determined.	
Ignition temperature:		
Decomposition temperature:	Not determined.	
Self-igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapour pressure:	Not applicable.	
Density at 20 °C:	$1,5 \text{ g/cm}^3$	

Printing date 17.10.2016

Revision: 18.07.2017

Trade name: KEMASAN 520

		(Contd. of page
· Relative density	Not determined.	
· Vapour density	Not applicable.	
· Evaporation rate	Not applicable.	
· Solubility in / Miscibility with		
water:	Soluble.	
· Partition coefficient (n-octano	I/water): Not determined.	
· Viscosity:		
Dynamic:	Not applicable.	
Kinematic:	Not applicable.	
· Solvent content:		
Organic solvents:	0,0 %	
VOC (EC)	0,00 %	
Solids content:	100,0 %	
• 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation
- Causes serious eye damage.
- · Respiratory or skin sensitisation
- May cause an allergic skin reaction.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- *Reproductive toxicity Based on available data, the classification criteria are not met.*
- STOT-single exposure Based on available data, the classification criteria are not met.
- $\cdot \textit{STOT-repeated exposure} \textit{ Based on available data, the classification criteria are not met.}$
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.

(Contd. on page 6)

EU

Printing date 17.10.2016

Revision: 18.07.2017

(Contd. of page 5)

Trade name: KEMASAN 520

· 12.3 Bioaccumulative potential No further relevant information available.

- 12.4 Mobility in soil No further relevant information available.
- \cdot Additional ecological information:

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach sewage water or drainage ditch undiluted or unneutralised.

· 12.5 Results of PBT and vPvB assessment

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

• 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

- **Recommendation:** Disposal must be made according to official regulations.
- Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information · 14.1 UN-Number · ADR, RID, ADN, ADN, IMDG, IATA Void · 14.2 UN proper shipping name Void $\cdot IATA$ · 14.3 Transport hazard class(es) · ADR, RID, ADN, IMDG, IATA Void · Class · Label -· 14.4 Packing group Void · ADR, RID, ADN, IMDG, IATA · 14.5 Environmental hazards: Not applicable. Not applicable. · 14.6 Special precautions for user · Stowage Category Α · Segregation Code SG35 Stow "separated from" acids. · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. · UN ''Model Regulation'': Void EU

(Contd. on page 7)

Printing date 17.10.2016

Revision: 18.07.2017

Trade name: KEMASAN 520

(Contd. of page 6)

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H335 May cause respiratory irritation.

· Department issuing SDS: R&D DEPARTMENT

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1A: Skin sensitisation - Category 1A STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Other informations: When cement reacts with water (for instance when making concrete or mortar) or becomes damp, a strong alkaline solution is produced. Due to its high alkalinity, damp cement may cause skin and eye irritation or burns. Because it contains soluble chromium (VI), it may cause an allergic reaction in individuals. A reducing agent for hexavalent chromium (Cr (VI)) under the limit of 0.0002% is added to cement if necessary.