

CERTIFICATE OF QUALITY**KEMABAND Y** corner element
Inside corner element of the sealing ribbon**PRODUCT DESCRIPTION**

Elastomeric, permanently elastic sealing expansion ribbon, width 120 mm, on polyester fabric, formed into the inside corner element, dimension 140 x 140 mm.

FIELD OF USE

For easier and safer sealing of joints and expansion joints on corners. For indoor and outdoor use.

PRODUCT DATA

Appearance	White-yellow ribbon
Packing	1 piece (25 pieces/box)
Storage and expiration date	Unlimited if stored properly in undamaged original sealed packaging in dry, cool conditions and protected against sunlight.

Technical data

Splitting pressure	0,70 bar
UV splitting pressure	0,60 bar
Longitudinal stretching force	26 N/15mm
Transversal stretching force	14 N/15mm
Longitudinal snap	290%
Transversal snap	180%
Transversal stretching at 25%	0,5 N/mm
Transversal stretching at 30%	0,6 N/mm
»Schältest«	0,3 N/10mm
UV resistance (200 h, 254-360 nm)	resistant (Mark 4-5)
Melting point	130°C/140°C

TEST REPORT

-

The document was issued with the intention to prove the quality of the product according to specific requirements.

Puconci, 12.12.2016

Head of R&D:

Stanko Polajner, univ.dipl.ing.met.

KEMA

Kema d.o.o.,

Puconci 393, 9201 Puconci, Slovenija

T: +386 (0)2 545 95 00 | F: +386 (0)2 545 95 10

I: www.kema.si | E: info@kema.si



CE