

# DECLARATION OF PERFORMANCE

*in accordance with Annex III to Regulation (EU) No. 182/2011. 305/2011  
amended by Delegated Regulation (EU) No. 574/2014*

Page 1 of 3

## Hidrostop Kit

DOP No.: 01 P5001 Hidrostop Kit

**1. Unique identification code of the product-type:**

Fast setting cement mortar, Hidrostop Kit

**2. Intended use/es:**

Cement fast-binding mortar for non-structural repairs

**3. Manufacturer:**

Murexin d.o.o.  
Puconci 393  
SI-9201 Puconci, Slovenia

**4. Authorised representative:**

Murexin AG  
Franz von Furtenbach Straße 1  
A-2700 Wiener Neustadt

**5. System/s of AVCP:**

4

**6.**

**a. Harmonised standard:**

SIST EN 1504-3:2006

Notified body/ies: -

**b. European Assessment Document / European Technical Assessment:**

-

Technical Assessment Body / Notified body/ies: -

**7. Declared performance/s:**

Essential characteristics	Performance	Harmonized technical specification
Compressive strength:	$\geq 25$ MPa	SIST EN 1504-3:2006
Chloride ion content:	$\leq 0,05$ %	
Adhesive bond:	$\geq 1,5$ MPa	
Restrained shrinkage / expansion:	NPD	
Carbonation Resistance:	NPD	
Elastic modulus:	NPD	



# DECLARATION OF PERFORMANCE

*in accordance with Annex III to Regulation (EU) No. 182/2011. 305/2011  
amended by Delegated Regulation (EU) No. 574/2014*

Page 2 of 3

Thermal Compatibility freeze-thaw:	NPD	
Capillary absorption:	NPD	
Reaction to fire:	Euroclass A1	SIST EN 13501-1
Dangerous substances:	complies	See SDS

## 8. Appropriate Technical Documentation and/or Specific Technical Documentation:

-

**The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.**

Signed for and on behalf of the manufacturer by:

Director: Bojan Ošep


Puconci, 30.09.2022



# DECLARATION OF PERFORMANCE

in accordance with Annex III to Regulation (EU) No. 182/2011. 305/2011  
amended by Delegated Regulation (EU) No. 574/2014

Page 3 of 3

		
<b>17</b>		
Murexin d.o.o. Puconci 393 SI-9201 Puconci		
<b>Hidrostop Kit</b> DOP No.: 01 P5001 Hidrostop Kit		
Essential characteristics	Performance	Harmonized technical specification
Reaction to fire:	A1	SIST EN 13501-1
Compressive strength:	$\geq 25 \text{ N/mm}^2$	
Adhesive bond:	$\geq 1,5 \text{ N/mm}^2$	
Chloride ion content:	$\leq 0,05\%$	
Restrained shrinkage / expansion:	NPD	SIST EN 1504-3:2006
Carbonation Resistance:	NPD	
Elastic modulus:	NPD	
Thermal Compatibility freeze-thaw:	NPD	
Capillary absorption:	NPD	
Dangerous substances:	Complies	See SDS
<b>EN 1504-3:2006</b> Cement fast-binding mortar for non-structural repairs		