

CERTIFICATE OF QUALITY**KEMABAND TACK 12**
Self-adhesive sealing ribbon**PRODUCT DESCRIPTION**

Self-adhesive, rubber-coated, butyl-based ribbon, width 120 mm. Waterproof, elastic even at low temperatures, resistant to alkaline substances, acids and salts.

FIELD OF USE

For sealing-off joints and dilatation joints in bathrooms, laundries or moisture-exposed surfaces with the waterproof coatings system HIDROSTOP ELASTIK, HIDROSTOP 94 and HIDROSTOP DP.

PRODUCT DATA

Appearance	Grey ribbon
Packing	10-metre roll
Storage and expiration date	24 months from date of production if stored properly in undamaged original sealed packaging in dry, cool conditions and protected against sunlight.

Technical data

Total width/widht of cover	120 mm	
Material weight	72 g/m	
Thickness	0,85 mm	
Resistance to temperature: min./ max.	-5°C/ +70°C	
Burst pressure max	0,4 bar	
Breaking load longitudinal	32,6 N/ 15 mm	
Breaking load lateral	23,3 N/ 15 mm	DIN 527-3
Extension break longitudinal	54,5 %	DIN 527-3
Extension break lateral	81,1 %	DIN 527-3
Power absorption at 25 % Elasticity lateral	0,96 N/mm	DIN 527-3
Power absorption at 50 % Elasticity lateral	1,33 N/mm	DIN 527-3
Peel test on neutral PVC carrier	> 10 N/ 20 mm	

TEST REPORT

- /

The document was issued with the intention to prove the quality of the product according to specific requirements.

Puconci, 01.02.2018

Head of R&D:

KEMA

Kema d.o.o.,

Puconci 393, 9201 Puconci, Slovenija

T: +386 (0)2 545 95 00 | F: +386 (0)2 545 95 10

I: www.kema.si | E: info@kema.si

Stanko Polajner, univ.dipl.ing.met.



KEMA d.o.o.
1

CE