

TECHNICAL DATA SHEET

KEMAPOX WHIPE, BLACK**Black felt pad**

PRODUCT DESCRIPTION	Interchangeable white felt pad, using for cleaning process of epoxy grout.
Field of use	After application of pure ARTCOLOR CLEANER and leaving them to sit for about 10–15 minutes, rubbing the surface with black felt KEMAPOX WHIPE.
Product properties	<ul style="list-style-type: none">• Suitable for cleaning float with dimension 12x25 cm• Thickness 20 mm

PRODUCT DATA**Basic information**

Appearance	Black felt
Packing	1 Piece

Technical data

Weight	32 g
Dimension	25 x 12 x 2,5 cm

LIMITATIONS

Data source: All technical data in this technical sheet was obtained by laboratory research. Actual data may differ due to different working conditions.

Local restrictions: Due to specific local regulations the installed product can differ from country to country. For exact instructions for use a country specific technical sheet should be obtained.

LEGAL BASE

Information and recommendations related to use of KEMA products are presented in good faith and believed to be correct. The later is based on our knowledge and experience with the products. Information is supplied upon the condition that products are stored and used according to the recommendations and the persons receiving the same will make their own determination as to its suitability for their purposes prior to use. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to information or the product to which information refers. In no event will KEMA be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information or the product to which information refers. Nothing contained herein is to be construed as a recommendation to the use any product, process, equipment or formulation in conflict with any patent, and KEMA makes no representation or warranty, expressed or implied that the use thereof will not infringe any patent. All orders fall under current sales and supply conditions. The user should always check the latest technical sheet available upon demand.